

## Slim Plug-In RTD Temperature Transmitter with Isolated Single/Dual Output

## DESCRIPTION

The MS3702B is a slim, plug-in RTD temperature transmitter that converts input signals from an RTD into commonly used DC signals and provides isolated single or dual output. This model is intended for measurement of narrow temperature spans, e.g. 30 to 50°C (Pt 100Ω input). It is therefore recommended to choose this for applications where a measuring temperature span is small.

**ORDERING CODE**[illegible]

## Output 2

**No code:** None

The codes are the same as for Output 1.

Note 1: When a voltage output is selected for Output 1 ,  
a current output cannot be selected for Output 2.

Note 2: When the code A (4 to 20mA) is selected for both of the two outputs, the output load will be 550Ω maximum for Output 1 and 350Ω maximum for Output 2.

Note 3: Upscale burnout protection is standard.

## Options

**No code:** None


**/L:** Dual current output with high output load

\* Not subject to CE approval.

(OUT-1: 750Ω / OUT-2: 550Ω)

**/X:** Others (Special order)

\* For non-standard options, ask MTT for availability.



## ORDERING INFORMATION

To place an order, please use the ordering code format as shown on the left. Also specify a measuring temperature range.

(e.g.) MS3702B-A-P1A6 (0 to 30°C)

\* Note that the temperature range should be specified in steps of at least 10 degrees Celsius.

Another Ordering Example:

For an output code of “0”: MS3702B-A-P106 (0 to 30°C / Output: 2 to 5V)

Note: If you wish to include multiple options in your order, specify the option codes in series (e.g. /LX).

## SPECIFICATIONS

## ● POWER SECTION

Power Requirements	100 to 240V AC: 85 to 264V AC (47 to 63Hz) 24V DC: 24V DC±10% 100 to 240V DC: 85 to 264V DC		
Power Sensitivity	Better than ±0.1% of span for each power supply range.		
Power Line Fuse	160mA fuse is installed (standard).		
Power Consumption			
Power	100-240V AC	24V DC	100-240V DC
Single Output	5.5VA max	1.6W max	6.0W max
Dual Output	7.0VA max	1.8W max	6.0W max

## ● INPUT SECTION

Excitation Current	Approx. 1mA with Pt for 0 to 100°C
Lead Wire Resistance	200Ω max. per wire

### Ranges Available

RTD	Temperature Range (°C)	Input Span	Input Bias
Pt 100Ω	-200 to +850	30 to 50°C	Up to 4x the input span.
JPt 100Ω	-200 to +500	30 to 50°C	
Pt 50Ω	-200 to +600	60 to 100°C	

Input Spec Ex.: For Pt 100 $\Omega$  (60 to 90°C), the input span is 30°C and the bias 60°C (2x the span).

## ● OUTPUT SECTION

Maximum Output Load		
Voltage Output (DC)	1V span and up	2mA max.
	10mV	10kΩ min.
	100mV	100kΩ min.
Current Output (DC)	4-20mA single output	750Ω max.
	4-20mA dual output	Output 1:
		550Ω max.
	Output 2:	
		350Ω max.
Zero Adjustment	Approx. ±5% of span. (Adjustable by the front-accessible trimmer.)	
Span Adjustment	Approx. ±5% of span. (Adjustable by the front-accessible trimmer.)	
Burnout Protection	Upscale (even if any of the three wires, A, B, and B' is opened)	
Ranges Available		
	Current Signal	Voltage Signal
Output Range (DC)	0 to 20mA	-10 to 10V
Output Span (DC)	4 to 20mA	10mV to 20V
Output Bias	0 to 100%	-100 to 100%
* For current output signals, the accuracy of any current output smaller than 0.1mA is not guaranteed.		
Output Spec Ex. 1: For 4 to 20mA output, the output span is 16mA and the bias +25%.		
Output Spec Ex. 2: For -1 to 4V output, the output span is 5V and the bias -20%.		

## ● PERFORMANCE

Accuracy Rating	Better than ±0.15% of span (at 25°C±5°C).
Temperature Effect	Better than ±1.0% of span per 10°C change in ambient.
Response Time	240ms max. (0 to 90%) with a step input at 100%.
CMRR	100dB min. (500V AC, 50/60Hz)
Isolation	4-way isolation between input, output [Output 1/Output 2], power, and ground.
Insulation Resistance	100MΩ min. (@ 500V DC) between input, output [Output 1/Output 2], power, and ground.
Dielectric Strength	Input / Output [Output 1/Output 2] / [Power, Ground]: 2000V AC for 1 minute (Cutoff current: 0.5mA) Power / Ground: 2000V AC for 1 minute (Cutoff current: 5mA) Output 1 / Output 2: 500V AC for 1 minute (Cutoff current: 0.5mA)
Surge Withstand Capability	Tested as per ANSI/IEEE C37.90.1-1989.
Operating Environment	Ambient temperature: -5 to 55°C Humidity: 5 to 90% RH (non-condensing)
Storage Temperature	-10 to 60°C

## ● PHYSICAL


Installation	Wall/DIN rail mounting
Wiring	M3.5 screw terminal connection (with a power terminal block cover & drop-out prevention screws)
Screwing Torque	0.8 to 1.0 [Nm] * Recommended
External Dimensions	W29 × H86 × D125mm (including the mounting screw and socket)
Weight	Main unit: 120g max. Socket: 80g max.

## ● MATERIALS

Housing	ABS resin (UL 94V-0)
Terminal Block	PBT resin (UL 94V-0)
Terminal Block Cover	PC resin (UL 94V-2)
DIN Rail Stopper	PP resin (UL 94HB)
Screw Terminal	Nickel-plated steel
Contacts Material and Finish	Brass with 0.2μm gold plating
Printed Circuit Board	Glass fabric epoxy resin (FR-4: UL 94V-0)
Anti-Humidity Coating	HumiSeal® 1A27NS (Polyurethane)

\* HumiSeal® is a registered trademark of Chase Corporation.

## TERMINAL ASSIGNMENT



①	P (+)	POWER
②	N (-)	
⊥	GND	
④	+ OUTPUT 1	
⑤	- OUTPUT 1	
⑥	N.C.	
⑦	+ OUTPUT 2	
⑧	- OUTPUT 2	
⑨	A RTD	
⑩	B RTD	
⑪	B' RTD	

## BLOCK DIAGRAM

